

## LUBRICANT



- + Jointing forces are minimised
- + Compatibility with other sealing materials
- + For plastic pipes
- + Various package sizes

### Lubricant - minimizing the jointing forces for plastic pipe laying

Lubricant is used to minimize the jointing forces when laying plastic pipes.


Lubricant is compatible with other sealing materials.




## INSTALLATION



Clean socket and spigot.



Apply lubricant to socket and spigot.



Push pipes together.

## TECHNICAL SPECIFICATION

Lubricant for minimizing the jointing forces for plastic pipe laying.

Pipe Material \_\_\_\_\_

Package Size \_\_\_\_\_

Article Number \_\_\_\_\_

\_\_\_ Qty \_\_\_ Price/Unit \_\_\_ Total

Manufacturer: MISSION RUBBER (UK) Ltd., Sheffield, S35 9TG, T +44 (0) 114 257 - 0040, F - 1122

Scope of Application: Plastic Pipes (White)

Packaging Size: White 250 ml Tube, 500 ml Tube, 1 kg Can

Standard/Approval: CE06, Safety Data Sheet (EU) No. 1907/2006



PRODUCT RANGE 

LUBRICANT				
Article Number	Reference	Pipe Material	Content Packaging	Weight (kg)
500110	Lubricant White 250 ml	for plastic pipes	250 ml Tube	0,3
500111	Lubricant White 500 ml	for plastic pipes	500 ml Tube	0,5
500112	Lubricant White 1 kg	for plastic pipes	1 kg Can	1,1